

## Cartridge Dust Collector

### How it Works

Dust laden air is drawn into dust collector through inlet due to suction created by exhaust fan and passes through filter cartridge elements, The abrasive resistant inlet promotes dropping out high particulate, generates uniform air flow, thus increase filter life. The dust gets deposited on outer surface of cartridges and clean air flows through the center passage of cartridge into clean air plenum. Clean air further exit into atmosphere through outlet duct. Cartridge are periodically and automatically get cleaned through air purging. Sequence circuit activates solenoid valves for high pressure air purging of preselected cartridges. Dust released from cartridges slides downward into the hopper for further collection into the dust bin.

### Special Features:

#### Downflow Principle :

Assures high collection efficiency.

#### Modular Design with no moving parts :

Low maintenance and replacement of cartridge element is easy and quick.

#### Fair Air to filter ratio :

Assures longer life of cartridges

#### Variety of fabric material :


Cartridges are normally of synthetic webbed material. However, other materials can be supplied to suit individual application.

#### Quality & reliability :

Dependable products with in-built quality for trouble free operation.

### Specification Sheet

Model Dustex™	Height mm	Width mm	Depth mm	Filter Area (sq. mtr.)	No. of Sole Value	Capacity Cfm. cub.ft./min. (cub.mtr/hr.)	Fan Motor HP (KW)
CT-1-1-10	1320	1660	605	16	1	500 (850)	1 (0.75)
CT-2-2-20	1870	1660	605	32	2	1000 (1700)	2 (1.5)
CT-3-3-30	2420	1660	605	48	3	1500 (2550)	3 (2.25)
CT-2-4-50	2030	1100	1525	64	4	2000 (3400)	5 (3.8)
CT-3-6-75	2460	1100	1525	96	6	3000 (5100)	7.5 (5.5)
CT-2-8-100	1280	1100	2320	128	4	4000 (6800)	10 (7.5)
CT-3-12-125	3440	1100	2320	192	6	5000 (8500)	12.5 (9.4)
CT-3-12-150	3440	1100	2320	192	6	6000 (10200)	15 (11.3)
CT-4-16-200	3870	1100	2320	256	8	8000 (13600)	25 (15)
CT-3-24-250	3440	2100	2320	384	12	10000 (17000)	20 (18.75)
CT-3-24-300	3440	2100	2320	384	12	12000 (20400)	30 (22.5)
CT-4-32-400	4520	2045	2320	512	16	16000 (27200)	40 (30)
CT-4-48-500	4200	3120	2320	768	24	20000 (34200)	50 (37.5)
CT-4-48-600	4200	3120	2320	768	24	24000 (40800)	60 (45)
CT-4-64-750	4520	4100	2320	1024	32	30000 (51000)	75 (56.3)
CT-4-80-1000	4520	5040	2320	1280	40	40000 (68000)	100 (75)



# NATIONAL ENTERPRISES

An ISO 9001:2008 Certified Co.

## Industrial

# Dust Collector



**NATIONAL ENTERPRISES**  
 MANUFACTURERS OF : Industrial Blast Rooms, Airless & Air Operated Abrasive Blasting Machines, Shot Peening Plants, Industrial Dust Collectors, Painting Equipments & Booths

ISO 9001:2008 ACCREDITED USA  
 AIAO-BAR ACCREDITED USA  
 CE

**CORPORATE & SALES OFFICE :** 12/2, Main Road, Opp. Lumax Automotive Systems Ltd., Nr. Sec-37 Modh, Faridabad -121003. Mob. : +91 8527923333, +91 9718383333 E-mail :- sales@nationalenterprises.org ; info@nationalenterprises.org

**REGISTERED ADDRESS:** A-1708, 1st & 2nd Floor, Green Fields, Faridabad - 121003, (Haryana)

**REGIONAL OFFICE PUNE:** Plot No. 81, Sector No. 10, PCNTDA, Bhosari Pune-411026 Maharashtra  
 Mob. : +91 9873770333, E-mail : pune@nationalenterprises.org

**Website:** www.nationalenterprises.org; www.shotblastingpainting.in

**Our Sales & Service Network - ❖ Faridabad ❖ Pune ❖ Jodhpur ❖ Ahmedabad ❖ Ludhiana ❖ Chennai**



ISO 9001:2008

# Eco Friendly

## Technology For A Sustainable Life


At NE we are harnessing technology to deliver more by utilising the minimum possible natural resource. Join us and be a part of this initiative for a greener tomorrow.

### Introduction of Dust Collector

Industrial Dust Collectors are in mandatory requirement to meet the pollution control norms for keeping the environment eco-friendly. Dust collectors separates any other dust particles from the blasting/thermal spraying / painting / grinding / buffing & clean air is out in the atmosphere.

# Cyclone Dust Collector

A cyclone dust collector is to separate any metallic or other dust particles from the spraying / Blasting room and discharge clean air to the atmosphere. In this suction created by Exhaust Fan caused the dust laden air to enter the Cyclone Dust Collector. In the cyclone the dust particles get separated by a centrifugal action and get settled in Dust Tray at the bottom of the cyclone. The dust free clean air escaped to the atmosphere through the Exhaust Fan. There by allowing dust to be collected in a dust tray at the bottom of the Cyclone Dust Collector is taken out manually, from time to time.




Model (Dustex)	Blower Capacity (CFM)	Motor (H.P)	Dimension							
			A	B	C	D	H1	H2	H3	W
CL-800	800	1.5	120	120	150	200	1590	1800	2050	660
CL-1500	1500	3.0	150	150	200	215	2100	2375	2690	710
CL-3000	3000	5.0	200	200	200	225	2710	3035	3370	830
CL-4000	4000	7.5	240	240	225	265	3330	3675	4055	940
CL-5000	5000	10.0	300	300	250	340	3900	4300	4720	1345

How the Multiclone Collector Works

## Multiclone Dust Collector

Multiclone is a primary collection with or without the optional after-filter, to separate dust of moderate to coarse particle size. The National Enterprises Multiclone will remove up to 90% (above 40 microns) of dust generated during blasting.



## Fabric Bag Dust Collector

How it Works



Dust laden air is drawn into dust collector through inlet due to suction created by exhaust fan and passes through fabric bags. Heavier dust particles fall into hopper due to loss of momentum. Finer dust gets deposited on inner surface of fabric bags and clean air passes across outer surface of filter bags and then exit into atmosphere through outlet. Bags are cleaned through motorised shaking arrangement. When motor is switched OFF, shaking cycle gets activated automatically and bags are shaken for preset time through timer. Dust released from filter bags slides downward into hopper for further collection into dust bin.

Special Features

- Modular Design with no moving parts : Low maintenance and replacement of fabric bags is easy and quick.

- Fair Air to filter ratio : Assure longer life of bags.


- Variety of fabric material : DUSTDUST Fabric bags are normally of cotton wovensatin cloth. However, other materials can be supplied to suit individual application.



# Specification Sheet

Model (Dustex)	Height mm	Width mm	Depth mm	Filter Area (sq. mtr.)	No. of Bags	Capacity Cfm cub. ft./min. (cub. mtr./hr.)	Fan Motor HP (KW)	Shaker Motor HP (QTY)
FB-36-75	5050	2000	1650	485	36	3000 (5100)	7.5 (5.5)	0.5 (1)
FB-48-100	5050	2400	1650	645	48	4000 (6800)	10 (7.5)	0.5 (1)
FB-60-125	5050	2800	1650	805	60	5000 (8500)	12.5 (9.3)	0.5 (1)
FB-72-150	5050	3200	1650	970	72	6000 (10200)	15 (11)	1 (1)
FB-96-200	5050	4000	1650	1290	96	8000 (13600)	20 (15)	1 (1)
FB-120-250	5050	4800	1650	1610	120	10000 (17000)	25 (18.5)	1 (1)
FB-144-300	5050	5800	1650	1940	144	12000 (20400)	30 (22)	1 (2)
FB-192-400	5050	7300	1650	2580	192	16000 (27200)	40 (30)	1 (2)
FB-240-500	5050	9000	1650	3220	240	20000 (34000)	50 (37)	1 (3)
FB-288-600	5050	11000	1650	3875	288	24000 (40800)	60 (45)	1 (4)
FB-360-750	5050	13000	1650	4830	360	30000 (51000)	75 (56.5)	1 (4)
FB-480-1000	5050	17200	1650	6440	480	40000 (68000)	100 (75)	1 (5)
FB-600-1250	5050	21300	1650	8050	600	50000 (85000)	125 (94)	1 (5)

\* These data are at 200 mm WC Static Pressure & are indicative only.



## Pleated Bag Dust Collector

How it Works

Dust laden air is drawn into dust collector through inlet due to suction created by exhaust fan and passes through Pleated Bag elements. The abrasive resistant inlet promotes dropping out high particulate, generates uniform air flow, thus increase filter life. The dust gets deposited on outer surface of Pleated Bag and clean air flows through the center passage of Pleated Bag into clean air plenum. Clean air further exit into atmosphere through outlet duct. Pleated Bag are periodically and automatically get cleaned through air purging. Sequence circuit activities solenoid valves for high pressure air purging of Preselected Pleated Bag. Dust released from Pleated Bags slides downward into the hopper for further collection into the dust bin.

Special Features :

- Fair Air to filter ratio :

- Assures longer life of cartridges

- Variety of material :

- Cartridges are normally of synthetic Webbed material. However, other materials can be supplied to suit individual application.

- Modular design with no moving parts.

## Typical Application for Ventilation & Dust Collection

- Shot Blasting Rooms.
- Metal and Powder Spraying Enclosures.
- Plasma Spray Acoustic Chamber.
- Smoke and Welding Fume Extraction.
- Wherever Dust extraction is a necessity.



## Specification Sheet

Model	Height mm	Width mm	Depth mm	Filter Area (sq. mtr.)	No. of Bags	No. of Sole Valve	Capacity Cfm cub. ft./min. (cub. mtr./hr.)	Fan Motor HP (KW)
PJ-12-75	6090	1500	1200	496	12	3	3000 (5100)	7.5 (5.5)
PJ-16-100	6090	1500	1500	661	16	4	4000 (6800)	10 (7.5)
PJ-20-125	6090	1800	1500	826	20	5	5000 (8500)	12.5 (9.3)
PJ-24-150	6090	2100	1500	992	24	6	6000 (10200)	15 (11)
PJ-32-200	6090	2700	1500	1322	32	8	8000 (13600)	20 (15)
PJ-40-250	6090	2700	1800	1652	40	8	10000 (17000)	25 (18.5)
PJ-50-300	6090	3300	1800	2065	50	10	12000 (20400)	30 (22)
PJ-60-400	6090	3900	1800	2478	60	12	16000 (27200)	40 (30)
PJ-75-500	6090	5000	1800	3100	75	15	20000 (34000)	50 (37)
PJ-100-600	6090	7700	1800	4130	100	20	24000 (40800)	60 (45)
PJ-120-750	6090	8900	1800	4956	120	24	30000 (51000)	75 (56.3)
PJ-150-1000	6090	10000	1800	6200	150	30	40000 (68000)	100 (75)
PJ-210-1250	6090	14000	1800	8670	210	42	50000 (85000)	125 (94)

\* These data are at 200 mm WC Static Pressure & are indicative only.



ISO 9001:2008



ISO 9001:2008